

# Silicon Diode

## **BYW96D**

800V/3A

# DATASHEET

OEM – Philips

Source: Philips Databook 1999

## Fast soft-recovery controlled avalanche rectifiers

## BYW96 series

### FEATURES

- Glass passivated
- High maximum operating temperature
- Low leakage current
- Excellent stability
- Guaranteed avalanche energy absorption capability
- Available in ammo-pack
- Also available with preformed leads for easy insertion.

### DESCRIPTION

Rugged glass SOD64 package, using a high temperature alloyed

construction. This package is hermetically sealed and fatigue free as coefficients of expansion of all used parts are matched.




Fig.1 Simplified outline (SOD64) and symbol.

### LIMITING VALUES

In accordance with the Absolute Maximum Rating System (IEC 134).

| SYMBOL      | PARAMETER                                    | CONDITIONS                                                                                                                          | MIN. | MAX. | UNIT               |
|-------------|----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|------|------|--------------------|
| $V_{RRM}$   | repetitive peak reverse voltage              |                                                                                                                                     |      |      |                    |
|             | BYW96D                                       |                                                                                                                                     | —    | 800  | V                  |
|             | BYW96E                                       |                                                                                                                                     | —    | 1000 | V                  |
| $V_R$       | continuous reverse voltage                   |                                                                                                                                     |      |      |                    |
|             | BYW96D                                       |                                                                                                                                     | —    | 800  | V                  |
|             | BYW96E                                       |                                                                                                                                     | —    | 1000 | V                  |
| $I_{F(AV)}$ | average forward current                      | $T_{ip} = 50\text{ }^{\circ}\text{C}$ ; lead length = 10 mm<br>see Fig.2;<br>averaged over any 20 ms period;<br>see also Fig.6      | —    | 3    | A                  |
| $I_{F(AV)}$ | average forward current                      | $T_{amb} = 55\text{ }^{\circ}\text{C}$ ; PCB mounting (see Fig.11); see Fig.3;<br>averaged over any 20 ms period;<br>see also Fig.6 | —    | 1.25 | A                  |
| $I_{FRM}$   | repetitive peak forward current              | $T_{ip} = 50\text{ }^{\circ}\text{C}$ ; see Fig.4                                                                                   | —    | 30   | A                  |
|             |                                              | $T_{amb} = 55\text{ }^{\circ}\text{C}$ ; see Fig.5                                                                                  | —    | 13   | A                  |
| $I_{FSM}$   | non-repetitive peak forward current          | $t = 10\text{ ms}$ half sine wave;<br>$T_j = T_{jmax}$ prior to surge;<br>$V_R = V_{RRMmax}$                                        | —    | 70   | A                  |
| $E_{RSM}$   | non-repetitive peak reverse avalanche energy | $L = 120\text{ mH}$ ; $T_j = T_{jmax}$ prior to surge; inductive load switched off                                                  | —    | 10   | mJ                 |
| $T_{stg}$   | storage temperature                          |                                                                                                                                     | -65  | +175 | $^{\circ}\text{C}$ |
| $T_j$       | junction temperature                         | see Fig.7                                                                                                                           | -65  | +175 | $^{\circ}\text{C}$ |

## Fast soft-recovery controlled avalanche rectifiers

## BYW96 series

### ELECTRICAL CHARACTERISTICS

$T_J = 25\text{ °C}$  unless otherwise specified.

| SYMBOL                           | PARAMETER                                    | CONDITIONS                                                                                                                 | MIN. | TYP. | MAX. | UNIT                   |
|----------------------------------|----------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|------|------|------|------------------------|
| $V_F$                            | forward voltage                              | $I_F = 5\text{ A}$ ; $T_J = T_{J\text{max}}$ ; see Fig.8                                                                   | —    | —    | 1.25 | V                      |
|                                  |                                              | $I_F = 5\text{ A}$ ; see Fig.8                                                                                             | —    | —    | 1.50 | V                      |
| $V_{(BR)R}$                      | reverse avalanche<br>breakdown voltage       | $I_R = 0.1\text{ mA}$                                                                                                      |      |      |      |                        |
|                                  | BYW96D                                       |                                                                                                                            | 900  | —    | —    | V                      |
|                                  | BYW96E                                       |                                                                                                                            | 1100 | —    | —    | V                      |
| $I_R$                            | reverse current                              | $V_R = V_{RRM\text{max}}$ ;<br>see Fig.9                                                                                   | —    | —    | 1    | $\mu\text{A}$          |
|                                  |                                              | $V_R = V_{RRM\text{max}}$ ; $T_J = 165\text{ °C}$ ;<br>see Fig.9                                                           | —    | —    | 150  | $\mu\text{A}$          |
| $t_{rr}$                         | reverse recovery time                        | when switched from $I_F = 0.5\text{ A}$<br>to $I_R = 1\text{ A}$ ; measured at<br>$I_R = 0.25\text{ A}$ ; see Fig.12       | —    | —    | 300  | ns                     |
| $C_d$                            | diode capacitance                            | $f = 1\text{ MHz}$ ; $V_R = 0\text{ V}$ ; see Fig.10                                                                       | —    | 75   | —    | pF                     |
| $\left  \frac{dI_R}{dt} \right $ | maximum slope of<br>reverse recovery current | when switched from $I_F = 1\text{ A}$ to<br>$V_R \geq 30\text{ V}$ and $dI_F/dt = -1\text{ A}/\mu\text{s}$ ;<br>see Fig.13 | —    | —    | 6    | $\text{A}/\mu\text{s}$ |

### THERMAL CHARACTERISTICS

| SYMBOL         | PARAMETER                                     | CONDITIONS          | VALUE | UNIT |
|----------------|-----------------------------------------------|---------------------|-------|------|
| $R_{th\ j-tp}$ | thermal resistance from junction to tie-point | lead length = 10 mm | 25    | K/W  |
| $R_{th\ j-a}$  | thermal resistance from junction to ambient   | note 1              | 75    | K/W  |




#### Note

1. Device mounted on an epoxy-glass printed-circuit board, 1.5 mm thick; thickness of Cu-layer  $\geq 40\text{ }\mu\text{m}$ , see Fig.11.  
For more information please refer to the 'General Part of Handbook SC01'.

# Fast soft-recovery controlled avalanche rectifiers




## BYW96 series

### GRAPHICAL DATA




# Fast soft-recovery controlled avalanche rectifiers

## BYW96 series




# Fast soft-recovery controlled avalanche rectifiers

## BYW96 series




Dotted line:  $T_J = 175^\circ\text{C}$ .  
Solid line:  $T_J = 25^\circ\text{C}$ .

Fig.8 Forward current as a function of forward voltage; maximum values.




$V_R = V_{RRMmax}$ .

Fig.9 Reverse current as a function of junction temperature; maximum values.



$f = 1\text{ MHz}$ ;  $T_J = 25^\circ\text{C}$ .

Fig.10 Diode capacitance as a function of reverse voltage; typical values.




Dimensions in mm.

Fig.11 Device mounted on a printed-circuit board.

Fast soft-recovery  
controlled avalanche rectifiers

BYW96 series



Input impedance oscilloscope: 1 MΩ, 22 pF;  $t_i < 7$  ns.  
Source impedance: 50 Ω;  $t_i < 15$  ns.

Fig.12 Test circuit and reverse recovery time waveform and definition.




Fig.13 Reverse recovery definitions.