

DIODES
COMPUTER DIODES (BY ASCENDING tRR)
GLASS PACKAGE

											Continued
	tRR	BV		IR			VF		C		Package
	ns	VOLTS	nA	@	VR	VOLTS	@	IF	pF		Equivalent
TYPE	MAX	MIN	MAX	@	VOLTS	MAX	@	mA	MAX	Package	DO-7/DO-35
1N4150	4.0	75	100	@	50	1.0	@	200	2.5	DO-35	1N3600
1N4305	4.0	75	100	@	50	0.85	@	10	2.0	DO-35	1N3063
1N4322	4.0	75	100	@	50	1.0	@	200	1.5	DO-7	
1N4454	4.0	75	100	@	50	1.0	@	10	2.0	DO-35	1N3064
1N4454 JAN	4.0	75	100	@	50	1.0	@	10	2.0	DO-35	1N3064
1N4454 JANTX	4.0	75	100	@	50	1.0	@	10	2.0	DO-35	1N3064
1N4532	4.0	75	100	@	50	1.0	@	10	2.0	DO-34	1N4454
1N5318	4.0	75	100	@	50	1.0	@	200	2.5	DO-34	FDH600
1N903	4.0	60	100	@	40	1.0	@	10	1.0	DO-7	
1N908	4.0	60	100	@	40	1.0	@	10	2.5	DO-7	
1N903A	4.0	50	100	@	40	1.0	@	20	1.0	DO-7	
1N904	4.0	50	100	@	30	1.0	@	10	1.0	DO-7	
1N907	4.0	50	100	@	30	1.0	@	10	2.5	DO-7	
1N907A	4.0	50	100	@	30	1.0	@	20	2.5	DO-7	
1N908A	4.0	50	100	@	40	1.0	@	20	2.5	DO-7	
FDH666	4.0	40	100	@	25	1.0	@	100	3.5	DO-35	
FDN666	4.0	40	100	@	25	1.0	@	100	3.5	DO-34	FDH666
1N905	4.0	40	100	@	20	1.0	@	10	1.0	DO-7	
1N906	4.0	40	100	@	20	1.0	@	10	2.5	DO-7	
1N4450	4.0	40	50	@	30	1.0	@	200	4.0	DO-35	
1N5319	4.0	40	100	@	25	1.0	@	100	3.5	DO-34	FDH666
1N904A	4.0	35	100	@	30	1.0	@	20	1.0	DO-7	
1N4009	4.0	35	100	@	25	1.0	@	30	4.0	DO-7	1N4154
1N4154	4.0	35	100	@	25	1.0	@	30	4.0	DO-35	1N4009
1N4536	4.0	35	100	@	25	1.0	@	30	4.0	DO-34	1N4154
1N905A	4.0	30	100	@	20	1.0	@	20	1.0	DO-7	
1N906A	4.0	30	100	@	20	1.0	@	20	2.5	DO-7	
1N3067	4.0	30	100	@	20	1.0	@	5	4.0	DO-7	
1N4727	4.0	30	100	@	20	0.85	@	10	4.0	DO-35	
1N4950	4.0	30	100	@	25	1.0	@	300	3.5	DO-7	
1N252	4.0	25	100	@	5	1.0	@	10		DO-7	
1N3596	4.0	20	100	@	20	1.0	@	30	1.0	DO-7	
FD6666	5.0	75	100	@	50	1.0	@	200	2.0	DO-7	
1N914 JAN	5.0	100	25	@	20	1.0	@	10	4.0	DO-7	1N4148
1N914 JANTX	5.0	100	25	@	20	1.0	@	10	4.0	DO-7	1N4148
1N3602	5.0	75	100	@	50	1.0	@	20	3.0	DO-7	
1N3603	5.0	45	100	@	35	1.0	@	30	3.0	DO-7	
1N4148 JAN	5.0	100	25	@	20	1.0	@	10	4.0	DO-35	1N914
1N4148 JANTX	5.0	100	25	@	20	1.0	@	10	4.0	DO-35	1N914
1N659	6.0	60	5	@	50	1.0	@	6		DO-7	
1N814	25	50	100	@	20	1.0	@	5	1.0	DO-7	
1N251 JAN	30	40	100	@	10	1.0	@	10	4.0	DO-7	
1N251	50	40	100	@	10	1.0	@	5	2.0	DO-7	

Preferred devices in bold type